

## Carat Tanks for drinking water Capacity of 2'200 to 10'000 liters



(Tank without holes, drilling on request)

**Special telescopic extension for drinking water tank. Top cover for pedestrian passage lockable with key. Lower cover with ventilation and insect filter.**

CHF 1'443.-- (Item. N° 381540)



**On request, it is possible to provide a structure with a cast iron cover for the passage of animals or small vehicles.**

CHF 1'740.--

### Extension

*Backfill height up to 1'500 mm, using 2 extensions of 300 mm between the dome and height adjuster.*

CHF 349.-- (Item. N° 371003)



**Ø 63 mm wall passage  
Special structure for drinking water.**

CHF 41.-- (Item N° 330035)



### Characteristics

Capacity (liters)	Length (mm)	Width (mm)	Height without dome (mm)	Height with dome (mm)	Weight (kg)	Item (N°)	Price Excluding VAT (CHF)
2'200	2'450	1'150	1'150	1'760	125	381130	1'995.--
3'350	2'450	1'400	1'400	2'010	150	381131	2'659.--
4'800	2'450	1'700	1'700	2'310	180	381132	3'464.--
6'500	2'450	2'000	2'000	2'610	260	381133	4'525.--
8'500	3'500	2'040	2'090	2'700	355	370604	4'816.--
10'000	3'520	2'240	2'290	2'900	410	370605	5'635.--

### Technical data

- Polyethylene monobloc tank certified food grade.
- Load capacity: Vehicles of less than 2.2 t with cast iron cover
- The "vehicles" overload on the pedestrian cover N° 381540 is not allowed.
- The pedestrian cover withstands a momentary load of 150 kg and a permanent load of 50 kg.
- The maximum depth of immersion in the water table is 80 cm with minimum covering of 80 cm.
- Set up : According to the manufacturer's guidelines.

### Tank modifications and adaptations in Canplast workshops

- Welding fittings for inlet or outlet pipes is possible in our manufacturing workshop.
- The position and diameter of the fittings are adapted to the client's specifications. It is also possible to install a drain plug and strainers.