



Platine Tanks for drinking water Capacity of 1'500 to 7'500 liters



(Tank without holes, drilling on request)

Special telescopic extension for drinking water tank.

Top cover for pedestrian passage lockable with key. Lower cover with ventilation and insect filter.

CHF 1'090.-- (Item. N° 381540)



On request, it is possible to provide a structure with a cast iron cover for the passage of animals or small vehicles. CHF 1'740.--

300 mm extension

Allows 300 mm of additional backfill height to be placed between the dome and the height adjuster.

CHF 349.-- (Item. N° 371003)



Ø 63 mm wall passage Special structure for drinking water CHF 41.-- (Item. N° 330035)



Characteristics

Capacity (liters)	Length (mm)	Width (mm)	Height without dome (mm)	Height with dome (mm)	Weight (kg)	Item (N°)	Price excluding VAT (CHF)
1'500	2'100	1'250	700	1'015	80	390600	1'496
3'000	2'450	2'100	735	1'050	170	390601	2'571
5'000	2'890	2'300	950	1'265	240	390602	3'643
7'500	3'600	2'250	1'250	1'565	360	390603	5'139

Technical data

- > Polyethylene monobloc tank certified food grade.
- Load capacity: Vehicles of less than 2.2 t with cast iron cover
- ➤ The "vehicles" overload on the pedestrian cover N° 381540 is not allowed.
- > The pedestrian cover withstands a momentary load of 150 kg and a permanent load of 50 kg.
- The maximum depth of immersion in the water table is 80 cm with minimum covering of 80 cm.
- Set up : According to the manufacturer's guidelines.

Tank modifications and adaptations in Canplast workshops

- Welding fittings for inlet or outlet pipes is possible in our manufacturing workshop.
- > The position and diameter of the fittings are adapted to the client's specifications. It is also possible to install a drain plug and strainers.